EG. \checkmark \checkmark \checkmark \land B C D $ANGLE$ ± 0.02 ± 0.05 ± 0.1 ± 0.2 $0 \sim 30^{\circ}$ $\frac{4}{2}$ ± 0.05 ± 0.1 ± 0.15 ± 0.5 $31^{\circ} \sim 60^{\circ}$ $\frac{4}{2}$ ± 0.15 ± 0.15 ± 0.2 ± 0.5 $61^{\circ} \sim 90^{\circ}$ $\frac{4}{2}$ 0 ± 0.15 ± 0.2 ± 0.25 ± 0.5 $61^{\circ} \sim 90^{\circ}$ $\frac{4}{2}$ 0 ± 0.15 ± 0.2 ± 0.25 ± 0.5 11.0 11.0 11.0 11.0	$\frac{1}{2}$			版次 修改内容 V0.1 第一次发行	修改 审核 批准 日
+@## ES 대象螢秋 Wa Smart Outdoor Camera S3 ES 대象螢秋專親島自己	H I U J A M M I U	1 1 <tr< th=""><th><text><text><text><text><text><text><text><text><text></text></text></text></text></text></text></text></text></text></th><th><text><text><text><list-item><image/><text><text><text><list-item><image/><image/><image/><image/><image/></list-item></text></text></text></list-item></text></text></text></th><th><text><text><text><text><text><text><text><text><text><text><text><text><text><text><text><text></text></text></text></text></text></text></text></text></text></text></text></text></text></text></text></text></th></tr<>	<text><text><text><text><text><text><text><text><text></text></text></text></text></text></text></text></text></text>	<text><text><text><list-item><image/><text><text><text><list-item><image/><image/><image/><image/><image/></list-item></text></text></text></list-item></text></text></text>	<text><text><text><text><text><text><text><text><text><text><text><text><text><text><text><text></text></text></text></text></text></text></text></text></text></text></text></text></text></text></text></text>
Image: Image	<text><text><text><text> Image: State Stat</text></text></text></text>	<text><text><text><text><text><text><text><text><text><text><text><text><text><text><text><text><text><text></text></text></text></text></text></text></text></text></text></text></text></text></text></text></text></text></text></text>	<text></text>		9999-099-097 : 現時 聖中福 1973-010-0594 ビビビーンSUITATE KOT 217-017-01111-125 第項意志可容性的事情理由的
成品尺寸: 120*90)mm				



H	G	F	E	D	C		В		A	/
		版次 V0.1		修改内容 第一次发行		修改	审核	批准	日期	
										\subset
										0
雙大音好幹武山添成手,元號qqA熟時,"+"鞋或qqA팭钉() 國本程時 qqA,gao, ^w e ¹ 。(黑亞的近郊特梨器由窗,洛公,亦手阴网通)中qqA至 20	Indicator Information Indicator status Description	未;内室于置数矿的坟口获派; ,水漏改驻武闭风 , 潔盖积範圍 80	注意: 摄像机使用DC电源接口供电时,请将BC电源体 使用DC电源接口供电话。 影响设备正常使用。		。	bottom facir	nstallation and adjustment, the camera speaker ng down position. Attach the installation positioning 9			
(海共口(2)((2)(10)(2)(10)(2)(10)(10)(2)(10)(10)(10)(10)(10)(10)(10)(10)(10)(10	Red light flashes slowly Waiting for configuration network Red light flashes quickly Connecting to the network Fixed red light Network anomaly Fixed blue light Successfully connected and running Blue light flashes slowly NVR online networking Micro SD Card Slot: Support micro SD card (Max 128G). Reset Button: Press and hold the reset button for 5 seconds to reset the			ORVIBO Home (3) Open the App and select "+", according to the App prompt, select the device type and model or scan the QR code above to add the device. (keep the phone, device and router close to each other when configuring the network). Tips (1) The camera only supports 2.4GHz Wi-Fi (5GHz is not supported). (2) When networking via wired, the camera and Mobile phone need to be	。齡水胡梁守司然,中奎水胡逝葵共說 。	世音塞頒水初心空料 ④	Install the screws Install expansion	n bolts		
 新送送式, (広気発変、 美焼肉油, 正在近河、 新聞、 MUA 在线声和(1286) 新聞、 SDF書, 大使主机, Freeded(#5, 4, 1286) SDF書, 大使主机, Freeded(#5, 4, 1286) SDF書, 大使主机, Freeded(#5, 4, 1286) SDF目、 SDF書, 大使主机, Freeded(#5, 4, 1286) SDF書, (第4, 1286) SDF書, 大支持1286, (重換, 小参量, 1286) SDF書, (1286) Pole Partition (1286) SDF目, (1286) SDE, (1286) SDE, (1286) Prime (1286) SDE, (1286) SDE, (1286) SDE, (1286) Prime (1286) SDE, (1286) SDE, (1286) SDE, (1286) SDE, (1286) SDE, (1286) SDE, (1286) Prime (1286) SDE, (1286) SDE, (1286) SDE, (1286) SDE, (1286) SDE, (1286) SDE, (1286) Difference (1286) SDE, (1286) Difference (1286) SDE, (1286) SDE, (1286) Difference (1286) SDE, (1286) SDE, (1286) SDE, (1286) Difference (1286) SDE, (1286) SDE, (1286) SDE, (1286) SDE, (1286) SD	 camera and restore factory settings. (To modify the camera network, you need to press and hold the reset button to restore the factory settings) PoE network port: If you connect the camera to a PoE router, the router will supply power and transmit data at the same time, but the power port cannot supply power. If you want to supply power by power port and transmit data by PoE power port, please connect the camera to a router without PoE function. * Note: After installing or removing the SD card or resetting the camera tighten the waterproof rubber plug at the bottom, otherwise the 	按概送时件中的膨胀螺栓安装型墙面。 表螺丝,将底座安装到墙面。	 (1) 选择合适的安装位置地面,在交装位置的装定和器位器机器位置的关键。 (1) 的位置打孔,孔直径约为两面,孔深约30mm。 (1) 计的计算 (2) 能提供机械转计紧安装回底座上,通过调节转向转行向 (3) 将摄像机流转拧紧安装回底座上,通过调节转向 	 connected in the same router. When switching the device Wi–Fi network, you need to press and hold the reset button for 5 seconds to reset the device, and follow the App prompts to add the device when the device indicator turns red and flashes slowly. Installation Notes ① Select a suitable installation location wall, paste the installation positioning sticker at the installation location, according to the		出口 新 新 M W 都 厳 計 ⑥ Waterproof 30d 俳 劇 新 与 新 M 熱 ⑦ 1. When the ca waterproof	Terminal Connection mera uses PoE network cable interface, please terminal fittings with hollow waterproof plugs. Ir	or indoors; inal, please overed to id affecting use the stall them		
息許tr元詳 明 说 恣状tr元韻 网猫許等 风射tr注 於网對其亦五 风射tr注 常果證网 亮常tr注	 waterproof ability of the equipment will be affected. Configuration Network Settings When the product is powered on, the camera automatically turns on. Scan the QR code below with your mobile phone, download and register to log in to the "ORVIBO Home" App. 02 	。不善	。 (如) (四) (四) (四) (四) (四) (四) (四) (四) (四) (四	 location marked on the positioning sticker to make the hole. The hole diameter is about 6 mm and the hole depth is about 30 mm. Install the expansion bolts in the accessories into the punched holes. 2 Rotate out the camera mounting base, use the mounting screws in the accessories to mount the base to the wall. 3 Rotate and tighten the camera back onto the base, and adjust the angle of the camera by adjusting the steering lever. 	7 政党,并强于端水税储整税水税企业用量,持口3 3 代税"的公式工会。 3 代防水税圈套在摄像机网线接口上。	中臺水坳亞邕影國왕① ① Pass the ne waterproof	shown below and make sure to tighten the wat sembly. twork cable through the waterproof cover, and p rubber ring on the camera network cable interfa	but the		04
										2
80					000-000	1 : 街自発號已裝安				
	Product failure or damages caused by force majeure such as earthquake, fire, flood lightning and so on. Product failure or damaged caused by any problem other than product design, technology, manufacturing, quality and others. Accessories are not included in free repair scope. This regulation shall come into effect since the issuing date. ORVIBO will keep the final interpretation right and revise.				気で被てA風聲山南号↑001首	www.orvibo.com service@orvibo.con				<u> </u>
; 社成短續效品 "內姓字等文火,震地 此素因 (元 而 下 不 感) (1) (1) (1) (1) (1) (1) (1) (1) (1) (1										
(內奈翁) 呆式 一個	08					7F, Block Xueyuan F				
										C
	制图 审	了核	批 准	产品名称	巨目智能室外摄像机	S3 中英文诉				
m ± 0.05 mm m ± 0.1 mm			ען עינ	产品料号				反本 \	/0.1	
m ±0.2mm MM	周宇婷				80 深圳	市欧瑞拉	重利拉服			<u></u>
				TEL:+86-0755-85277097						۰ F

